

DESIGN

Tineke Beunders & Nathan Wierink

PRODUCT CATEGORY

Ceiling light

ENVIRONMENT

Indoor

MATERIAL

Copper plated steel, silicone

STOCK ITEM

Copper

COLOR ZONES

One color zone, including remote control.

CABLE LENGTH

4 meter

CUSTOM POSSIBLITIES

For complete custom made configurations we refer to our CONTOUR custom system.

PRODUCTION PROCESS

The frame is made from extruded steel profile and copper plated. The LED lighting is fixed in the profile and filled with a diffuse silicone. All parts are tested, mounted and packed inhouse (Aptum, Eindhoven, NL).

DIMENSIONS

W: 145cm/ 57.1in x D: 72cm/ 28.4in x H: 10cm/ 3.9in.

PACKAGING DIMENSIONS

W: 141cm/ 55.5in x D: 74cm/ 29.1in x H: 5,5cm/ 2in.

WEIGHT

Product: $6kg/13,2lbs \mid Incl packaging: 8kg/17,6lbs.$

DELIVERY

Flatpack with instructions to assemble.

COLLI QUANTITY

1 set

VOLTAGE

24 Volt \mid suitable for 220-240V.

WATTAGE

Max. 52 Watt \mid Average 26 Watt.

LUMEN

108-168 depending on controller type.

LIGHT SOURCE & ENERGY EFFICIENCY CLASS

RGB-LED, color adjustable, dimmable. The luminaire contains built-in LED lamps. Energy class: A ++ to A.

CERTIFICATIONS

CE, IP 20, 🗆

OPTIONAL


Philips Hue controller Ceiling solution

CLEANING INSTRUCTIONS

Switch off the electricity supply before cleaning. Clean with soft dry cloth.

APTUM X GOLDEN HOUR









Configuration Golden hour

