

DESIGN

Tineke Beunders & Nathan Wierink

PRODUCT CATEGORY

Wall light

ENVIRONMENT

Indoor

MATERIAL

Coated steel, silicone

STOCK ITEM

Soft White - RAL 9016

SETTINGS

3 modes: Completely warm white \mid Gradient mode (4 settings) \mid Twinkle mode (6 settings).

CABLE LENGTH

4 meter

CUSTOM POSSIBLITIES

For complete custom made configurations we refer to our CONTOUR custom system.

PRODUCTION PROCESS

The frame is made from extruded steel profile and powder coated. The LED lighting is fixed in the profile and filled with a diffuse silicone. All parts are coated, tested, mounted and packed in-house (Aptum, Eindhoven, NL).

DIMENSIONS

W: 60cm/ 23.6in x D: 8cm/ 3.1in x H: 61,5cm/ 24.2in. / W: 75cm/ 29.5in x D: 8cm/ 3.1in x H: 76,5cm/ 30.1in.

PACKAGING DIMENSIONS

W: 70cm/ 27.6in x D:12cm/ 4.7in x H: 70cm/ 27.6in. / W: 85cm/ 33.5in x D:12cm/ 4.7in x H: 85cm/ 33.5in.

WEIGHT

Product: 2,5kg/ 5.5lbs \mid Incl packaging: 5kg/ 11lbs. / 3kg/ 6.6lbs \mid Incl packaging: 5,5kg/ 12,1lbs

DELIVERY

Flatpack with instructions to assemble.

COLLI QUANTITY

1 рс

VOLTAGE

5 Volt | suitable for 220-240V.

WATTAGE

Max. 11 Watt | Average 5 Watt.

LIGHT SOURCE & ENERGY EFFICIENCY CLASS

RGB-LED, color adjustable, dimmable. The luminaire contains built-in LED lamps. Energy class: A ++ to A.

CERTIFICATIONS

CE, IP 20, □

CLEANING INSTRUCTIONS

Switch off the electricity supply before cleaning. Clean with soft dry cloth.









Configuration living circle

